



CONCRETE FINISH

ULTRATEX Concrete Finish is an aesthetically pleasing smooth finish material, giving the appearance of a concrete panel look. It is an acrylic based coating that is flexible and manufactured using quality graded quartz, 100% acrylic emulsions, and other additives blended together, which can be used over many substrates. Available in grey, and white which can be tinted to colour of choice.

Features

- Water based
- Ease of use
- Vapour permeable

Benefits

- Tough
- Flexible
- Water resistant
- Excellent adhesion
- Long term exterior protection

Uses

- ULTRATEX Concrete Finish is suitable for application over properly prepared substrates such as brick, block, cement render, ULTRATEX Render, concrete, cement sheeting, and plasterboard.
- Can be used interior and exterior.

Colours and Gloss

- Can be tinted to a wide range of colours achieving a natural finish.
- Low Sheen when over coated with ULTRATEX Sealer.

Coverage Rate	APPROX. 20 m ² per 20kg bag for 1 coat Coverage rates may vary according to substrate and preparation.
Application Method	Hawk and trowel
Dry Film Build	Approximately 0.25mm per coat
Wet Film Build	

Typical Data at 25°C and 50% Relative Humidity	Drying Time	24 hours
Touch Dry	2 hours	
Dry to Recoat	4 hours	
Usual No Coats	2	
Clean Up	Water	
Packaging Sizes	20kg bag	
Volume Solids		
Thinning	Up to 5%	
Abrasion Resistance	Excellent	



Substrate Conditions

- ULTRATEX Concrete Finish must be applied over properly prepared substrates that are free of dirt, dust, grime and any other contaminants
- Substrates must not contain more than 15% WME prior to application
- Do not apply if air and surface temperatures are below 5°C or above 35°C
- If applying over ULTRATEX Quick Render, application may proceed after 48 hours if properly cured
- Fresh cementitious substrates such as site mix sand and cement render and concrete must be left for up to 28 days to sufficiently cure prior to application of ULTRATEX Concrete Finish
- ULTRATEX primer should be used when applying over site mix render.

Application

- Check colour before use.
- Ensure same batch numbers are used on a single wall where possible.
- Apply evenly over the properly prepared substrate with a hawk and trowel
- Ideally apply slightly thicker than the granules to achieve optimum results.
- Finish with a steel or Venetian trowel.
- Be sure to keep a wet edge with this product and plan your work to suit the product and weather conditions.
- If joining up to previous day's application, start and finish on an external or internal corner.
- Keep sheltered from rain & moisture for 24-48 hrs. after completion dependent on climatic conditions.
- It is advisable to apply a primer before the application of ULTRATEX Concrete Finish.
- Over coat with 2 coats of ULTRATEX Sealer

Precautions and Limitations

- Check colour before use.
- Ensure same batch numbers are used on a single wall where possible.
- Should not be applied in temperatures below 5°C or above 35°C.
- Not suitable for areas of continual damp or areas submerged in water

Transport and Storage

- Store in a cool dark place
- Keep sealed

Disposal

- Dispose of in accordance with local council regulations



Safety Data

Refer to ULTRATEX Concrete Finish SDS

Disclaimer

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, expressed or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use. ULTRATEX WALL CLADDING & COATING shall not be responsible for the use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. User is responsible for determining appropriate safety measures and for applying the legislation covering his own activities. We recommend that user makes tests to determine the suitability of a product for its particular purpose prior to use.