



### Ultratex Roll-On Texture

### TECHNICAL DATA SHEET

#### **Description**

Ultratex Roll-On Texture is a pre-mixed acrylic granular high build coating supplied in range of tint able bases as well as pre-coloured form. This premium exterior grade product consists of premium water based acrylic emulsion, high grade pigments, fillers, sand, marble and powerful fungicide/ anti- mildew agent. It is available in two Grades; "Fine" & "Coarse".

#### **Uses**

Ultra-Roll-On Texture is a durable sand/marble-based texture coating, ideal for providing an attractive finish coating on correctly prepared exterior & interior wall surfaces of domestic & commercial buildings. Generally, it is roller applied with either fine texture roller or coarse roller to achieve a fine or coarse stipple texture or with stipples being flattened with a steel trowel, this coating has excellent resistance to weathering and excellent exterior durability. It requires to being top coated with Ultratex Membrane for total exterior durability and performance.



#### **Features and Benefits**

- Strong adhesion, Resistance to Mold and Algae
- Excellent flexibility, crack resistance and has good vapour permeability, tint-able to extensive colour range, Easy to apply, Water based

#### **Suitable Substrates – when properly prepared**

- Cement Render surfaces
- Rendered ACC and Fire cement Sheeting
- Rendered Polystyrene Panels (EPS)
- Rendered Clay and Concrete Brickwork & Block
- Other primed exterior surfaces

#### **Surface preparations**





- Areas not to be coated should be masked and protected.
- All surfaces to be coated must be dry, clean, sound, free from contaminants including; oil, mold release, dust, dirt, silicone, mud, grease, salt, efflorescence, animal droppings and any loose or flaking material.

#### **Application**

Mix thoroughly with a power mixer, ensure product colour and consistency before application.



- Apply using specific roller coat of texture with a fine texture roller for the “Fine” grade or coarse texture roller for the “Coarse” grade
- If stipple effect is required leave as is, if flattened effect is required, allow the material to stand for some time, check if surface is dry enough, flatten stipples with a wet steel trowel with a light hand such that you do not drag the texture surface and damage or disturb the rolled layer.
- Let the Texture dry for 24 hours; there after applying one coat of Ultratex Membrane to ensure system durability and performance.

Roll-On Texture Grade	Packing	Coverage/ Pail	Thk
Fine	15L Pail	14-15 SqM	Grain Size
Coarse	15L Pail 	8-10 SqM	Grain Size
Application Tools	<b>Fine Grade</b> -  Fine Texture Roller (Black) <b>Coarse Grade</b> -  Spaghetti Coarse Texture Paint Roller (Green)		
Clean Up	 Clean all with water after use		
Appearance	Coloured gritty viscous liquid paste		
Type	Acrylic emulsion		
Drying Time (25°C & 50% RH)	Tack Free	Over-coat	Fully Dry
	3Hrs	24hrs	7 days
WFT	Grain Size		
No. of coats	Generally single coat		
Gloss levels	Matt		
Specific Gravity	~ 1.5-1.8		
Thinner	Water – not recommended		
Shelf Life	24 months from date of mfg (sealed)		

### Important Information

Roll-On Texture must only be applied in air temperatures between 10°C and 30°C on a dry substrate and must be protected from rain and frost for the first 24 hours or finished work must be protected from rain, frost and severe weather conditions until fully dried. Avoid application in full sun or hot, windy conditions.

### Safety and Handling

**Refer to Material Safety data sheet and warranty document before use;**

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact. Wear protective clothing to minimize skin contact and wear goggles where splatter is likely. Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner.

Storage: Store away from food and drink and in a safe place

For further information on *Warranty & Limitations* or *Material Safety Data Sheet* for Ultratex Roll-On Texture, please call (03) 9364 4489 or visit [www.Ultratexvic.com.au](http://www.Ultratexvic.com.au)